


REMARKS

The purpose of this Preliminary Amendment is: (1) To provide a Substitute Specification and an Abstract which are in formats customary for U.S. Patent Applications and which are also expressed in less stilted and more readable idiomatic english; (2) To amend the claims in this Application to eliminate multiple-dependent claims therefrom; (3) To establish a Filing Fee; and (4) To amend the claims so that they are more nearly in a format customary of U.S. Patent Applications. It is to be understood, nevertheless, the claims originally set forth remain part of the original disclosure with the Application. As amended, the Application has thirty (30) claims, three (3) of which are independent claims. Accordingly, a Filing Fee of \$435.00 appears to be required, and our check to cover same is submitted herewith. If this is in error, the Commissioner of Patent and Trademarks is authorized to debit or credit our Account No. 13-2000 as appropriate.

Respectfully submitted,

MASON, MASON & ALBRIGHT

By 

Penrose Lucas Albright
Registration No. 19,082

2306 South Eads Street
Post Office Box 2246
Arlington, Virginia 22202
Tel. (703) 979-3242

Filed: August 22, 2000
Attached: Substitute Specification and
marked-up copy for comparison
Abstract of Disclosure

002280-82824960


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A01K 5/02	A1	(11) International Publication Number: WO 00/38505 (43) International Publication Date: 6 July 2000 (06.07.00)
(21) International Application Number: PCT/NL99/00791 (22) International Filing Date: 21 December 1999 (21.12.99) (30) Priority Data: 1010898 24 December 1998 (24.12.98) NL (71) Applicant (for all designated States except US): MAASLAND N.V. [NL/NL]; 10 Weverskade, NL-3155 PD Maasland (NL). (72) Inventor; and (75) Inventor/Applicant (for US only): VAN DEN BERG, Karel [NL/NL]; 5 Boterbloemstraat, NL-2971 BR Bleskensgraaf (NL). (74) Agent: CORTEN, Maurice, Jean, F., M.; 10 Weverskade, NL-3155 PD Maasland (NL).		(81) Designated States: AU, CA, IL, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. In English translation (filed in Dutch). 8553/189 Mark up com

(54) Title: A FEEDING AND/OR DRINKING COLUMN ON BEHALF OF ANIMALS

(57) Abstract

A feeding and/or drinking column for animals, such as cows or goats, said column comprising a central axis surrounded by several reservoirs (3) and feeding troughs (6), as well as at least one metering device (5) for dosing feed and/or drink from at least one of the reservoirs (3) to at least one of the feeding troughs (6), while the feeding and/or drinking column is provided with a framework (1) located around the central axis, to which framework (1) primarily the feeding troughs and reservoirs (3) are fitted.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LJ	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

RELATED APPLICATION: *Inventor's*
This a continuation of Application No. PCT/NL99/00791
filed December 21, 1999.

A FEEDING AND/OR DRINKING COLUMN ON BEHALF OF ANIMALS

FIELD OF THE INVENTION:

The invention relates to a ^{COLUMN for} ~~feeding and/or drinking~~ ^{or both} ~~column~~ ^{by} for animals, such as cows, said column comprising a central axis surrounded by several reservoirs and feeding troughs, as well as at least one metering device for dosing feed ~~and/or drink~~ ^{liquid} from at least one of the reservoirs to at least one of the feeding troughs.

BACKGROUND OF THE INVENTION:

Such a feeding and/or drinking column is known.
 A disadvantage of ~~this~~ ^{known} construction is the size of the feeding and/or drinking column as a result of which the latter occupies much space in the shed. Furthermore, ~~the production of~~ ^{its construction is} the feeding and/or drinking column entails high costs because ~~there are used components that vary per feeding and/or drinking~~ ^{are used are quite variable} column, depending on the number of animals to be fed and the specific wishes of the user.

SUMMARY OF THE INVENTION:

On object of the invention ^{is to} ~~The invention aims at~~ ^{above} obviating the ~~drawbacks~~ ^{drawbacks}. For that purpose the ~~feeding and/or drinking~~ ^{column for} ~~column~~ ^{or both} is provided with a framework located around the central axis, to which framework primarily the feeding troughs and reservoirs are fitted. In this manner ~~there is achieved a~~ ^{res} construction occupying little space. ~~The compactness~~ ^{res} may be increased in that a cross-section of the framework perpendicular to the central axis is substantially circular. There is also obtained a great accessibility of the feeding troughs in that the circumference of the feeding column is substantially circular. This makes it possible for the livestock to reach the feeding troughs ^{column for} easily from all directions. In this manner the capacity of the ~~feeding and/or drinking~~ ^{or both} ~~column~~ can be utilized as efficiently as possible.

The ~~feeding and/or drinking~~ ^{column for} column is provided with partitions disposed between the feeding troughs and having such dimensions that they prevent the animals from disturbing each other during eating or drinking, ^{from} or eating one another's feed. In this manner the animals are able to eat quietly, without being distracted by animals in the vicinity of the feeding troughs. The shortest distance between two adjacent partitions

equals approximately the width of the outside of the feeding trough. Thus there is again achieved a great compactness of the feeding column. In a preferred embodiment of the invention, the number of partitions equals the number of feeding troughs.

5 The ~~feeding and/or drinking~~ ^{in accordance with the invention} column can easily be assembled because ~~one or more~~ components fitted to the framework are detachable. One or more components can be disassembled without tools being used, so that they can easily be fitted to the framework and be removed therefrom. The aforementioned
10 components ~~comprise a partition and/or a reservoir and/or a feeding trough~~ ^{or a combination thereof}. Finally a component may also comprise a metering device. In this manner the ~~feeding and/or drinking~~ column can easily be adapted to the user's wishes. Exchanging components is also very simple and the ^{column's} capacity ~~of the feeding and/or drinking~~
15 ~~column~~ can be utilized optimally and efficiently.

~~The components of at least~~ ^{at least one} subset of ~~the~~ ^{via} components is similar in shape. Because of the fact that the ~~feeding and/or drinking~~ ^{of the invention} column consists of uniform components, said components can be produced in large numbers, ~~so that~~ ^{whereby} the production costs remain
20 low.

In a preferred embodiment of the invention, ~~the~~ ^a storage room is located above the feeding troughs. As a result thereof a separate drive unit for transporting the feed is not required, as the gravitational force causes the feed to flow from the
25 storage room to the feeding troughs. The metering device is preferably located in the middle of a cross-section perpendicular to the central axis of the framework so as to be able easily to serve the feeding troughs. Due to the fact that the reservoirs are almost contiguous they occupy little space.
30 For the purpose of filling the reservoirs, the latter are provided with a ^{opening to} filling aperture. The feeding troughs are almost contiguous as well, so that ~~the~~ ^a maximum number of feeding troughs can be disposed along the circumference of the ~~feeding and/or drinking~~ column. In a preferred embodiment of the
35 invention, the number of feeding troughs equals the maximum

number of animals to be fed that are able to position themselves side by side along the circumference formed by the totality of feeding troughs.

In a preferred embodiment of the invention, at a specific radius of the circular circumference of the framework the number of feeding troughs for feeding cows ¹⁰~~amounts~~ to twelve.

According to another inventive feature, the ~~feeding and/or drinking~~ column is provided with at least one weighing device which is suitable for being used in a feeding trough ^{or both} and/or a metering device. By means of said weighing device it is possible to ^{regulate}~~establish~~ the amount of feed in the metering device ^{or both} and/or the feeding trough. At least part of the weighing device is in particular movable about a central axis. Therefore, one or more weighing devices that can be used both for the metering device and for one or more feeding troughs, will suffice. This has the advantage that the cost of ^{several}~~some~~ weighing devices can be saved.

According to an inventive feature, the metering device is disposed between at least one reservoir and at least one feeding trough. In this manner it is achieved that the feed ~~can~~ flows by gravitational force from a reservoir via the metering device to the feeding trough, so that ^{not}~~are~~ separate drive means are required. The metering device comprises at least one storage room, so that the feed or the ingredients thereof are not directly supplied to a feeding trough. The metering device may also comprise mixing means for mixing the material present in the storage room. The animals are thus prevented from eating selectively only specific feed ingredients. In a preferred embodiment of the invention, the metering device is movable about a central axis, and in particular rotatable about this central axis, so that it is possible to serve several feeding troughs by means of the metering device. To that end, according to an inventive feature, for moving the metering device the latter is provided with a drive unit.

In accordance with the invention, the feeding ~~and/or drinking~~ column, further comprises removing means for removing substances that are unfit for consumption from the flow of feed. In this manner undesired feed ingredients, such as metal objects and plastics, can be removed from the feed. The removing means comprise at least one magnet ~~and/or at least one electromagnet~~ ^{or any combination thereof} ~~and/or at least one reel~~. With the reel it is possible to remove metal objects from the flow of feed by means of eddy currents.

The ~~feeding and/or drinking~~ column ^{in accordance with the invention} is provided with identification means for identifying an individual animal, while the column is capable of operating fully automatically. According to an inventive feature, before the animals are fed by means of the ~~feeding and/or drinking~~ column, the individual animal is identified, after which, by means of the metering device, the feed is composed of ingredients emanating from one or more reservoirs, according to the nutritive needs of the individual animal, and the feed is supplied to the feeding trough. By means of a weighing device in the metering device, the amount of feed ~~can be~~ ^{corresponds} ~~attuned~~ to the nutritive needs of the individual animal. In accordance with another inventive feature, during pouring the feed into a feeding trough, the amount of feed is ~~attuned~~ ^{correlated} to the nutritive needs of the individual animal by means of a weighing device. Finally the amount of feed can also be ~~attuned~~ ^{made to correspond} to the nutritive needs of the individual animal by means of ~~the~~ ^a weighing device in a feeding trough. Depending on the location of one or more weighing devices in the ~~feeding and/or drinking~~ column and the assembly of the various components of ~~the feeding and/or drinking~~ ^{the} column, various configurations of various components are possible, while in the various configurations the weight of the feed supplied can each time be determined.

By means of ~~the~~ ^a weighing device, which is in connection with the feeding trough, the eating speed of an animal is ~~determined~~ ^{established} and the value thereof is subsequently stored in a ~~memory~~ ^{computer} memory. The nutritive needs of the individual animal ~~are~~ ^{are}

determined with the aid of one or more values stored in a ^{computer} memory and relating to the eating speed of the individual animal. The eating speed of an animal having ~~A~~ great nutritive needs will be considerably higher than that of an animal having ~~a~~ small nutritive needs. The small nutritive needs may result for example from an animal's illness. ^{thus} the eating speed also relates to the animal's condition. According to a last inventive feature, the feed that has not been consumed by the individual animal is automatically removed from the feeding trough with the aid of removing means.

BRIEF DESCRIPTION OF THE DRAWINGS:

The invention will now be explained in further detail with reference to the figures.

Figure 1 is a side ^{elevation} view of the framework ^{for the main column} provided with a storage room;

Figure 2 is a plan view of the framework according to cross-section ^{taken a line in Figure 1} II-II; ^{broken vertical}

Figure 3 is a cross-sectional view of a feeding ^{a column for} and/or drinking ^{or both in a column with the invention} column, and

Figure 4 is a plan view of ^{the} a feeding and/or drinking column ^{of the invention} provided with several reservoirs.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the embodiment shown in Figure 1, ^a ~~the~~ framework 1 has a substantially circular circumference. At the upper side of ~~the~~ framework 1 ~~there is located~~ a storage room 2, consisting of several reservoirs 3. On ~~the~~ framework 1 ^{facilities} ~~there~~ are provided ~~facilities~~ for placing ~~the~~ reservoirs 3.

~~The~~ Framework 1 is also provided with partitions 4 which are detachably arranged on ~~the~~ framework 1. ~~The~~ Framework 1 is preferably designed as a steel tubular construction.

^{of Figure 1} Figure 2 is a cross-section ^{taken on 3} according to the line II-II. ~~The~~ Framework 1 is divided into three segments per quarter. In this embodiment, ^a ~~total of~~ twelve cows can be fed at the same time.

*vertical balance**in accordance with the invention*

Figure 3 is a cross-section of the feeding column, showing ~~the~~ framework 1, ~~the~~ reservoirs 3, ~~the~~ partitions 4, ~~the~~ metering device 5 which may be provided, if desired, ~~with~~ a storage room, ~~the~~ feeding troughs 6, identification means 7 and a drive unit 8 for ~~the~~ metering device 5. Because of the cylindrical geometry of the ~~feeding and/or drinking~~ column the construction occupies little space, while ~~the feeding and/or drinking~~ column is optimally accessible to the animals from all directions. In ~~the~~ metering device 5 there is disposed an electromagnet 9 by means of which metal objects ~~can be~~ ^{are} removed from the flow of feed.

of the invention
Figure 4 is a plan view of the ~~feeding and/or drinking~~ column, showing ~~the~~ reservoirs 3 with filling apertures 10, ~~the~~ framework, 1 and ~~the~~ partitions 4.

Although I have disclosed the preferred embodiment of my invention, it will be understood by those skilled in the art that it is capable of other adaptations and modifications within the scope of the following claims: